

TEKNOALU-TAPE

Aluminium adhesive adesive tape

DESCRIPTION

Teknoalu-tape is mainly used in industrial HVAC applications. It has excellent mechanical strength and is easy to use when working indoors at low temperatures.

It also has a strong adhesiveness and guarantees excellent resistance to water and steam.



TAPE COMPOSITION

- Base: fired aluminium film, thickness 30 μ
- Glue: transparent synthetic
- Cover: polyethylene anti-adhesive protective film

STANDARD DIMENSIONS

- Pack. 24 rolls: 50x50 mm
- Pack. 16 rolls: 50x75 mm
- Pack. 12 rolls: 50x100 mm

Other sizes are available on request.

PROPERTIES	STANDARD	UNIT	VALUE
SUPPORT SHIM	DIN EN 1942	μ	30 +/-10 %
BREAKAGE ELONGATION	DIN EN 1941	%	> 10
ADHESION ON STEEL	DIN EN 139	N/cm	6
OPERATING TEMPERATURES		C°	-40° + 120°
APPLICATION TEMPERATURES		C°	-20° + 40°

It is essential that the surface on which the tape will be applied is free of any contaminating agents, such as dust, oil, grease or water.

Use

The products are packaged in cardboard boxes or plastic cases (according to the type).

The product identification codes are labelled on each package.

Storage

You are advised to store the product in adry, closed location, protected from atmospheric agents.



Reference standard:
En 14303:2009+A1:2013
Certificate No. 0407-CPR-1230.

TEKNISOL srl
via 1° Maggio, 38/38A - 20028 San Vittore Olona
Milano – Italia | 0039 0331 514605 | info@teknisol.it

