

TEKNORUBBER-TAPE

Anti-condensate adhesive elastomer tape

DESCRIPTION

Teknorubber-Tape is a closed cell expanded elastomer tape, characterised by high flexibility, ideal for thermal insulation both hot and cold.

It offers an effective combination of low thermal conductivity, high resistance to water vapour diffusion and reduced flame propagation.



TAPE COMPOSITION

- 3 mm thick elastomer
- Double-sided mesh adhesive, paper or liner finish

STANDARD DIMENSIONS

- Pack 24 rolls: 50x3x10 m
- Pack 12 rolls: 100x3x10 m

15 m length is also available

PROPERTIES	STANDARD	UNIT	VALUE
DIMENSIONAL TOLERANCES	IN 14304		
THICKNESSES		mm	3
WATER ABSORPTION	IN 13472	%	< 0,1
MAXIMUM SERVICE TEMPERATURE		C°	85° – 40°
LENGTH		m	10 - 15

It is essential that the surface on which the tape will be applied is free of any contaminating agents, such as dust, oil, grease or water.

Use

The products are packaged in cardboard boxes or plastic cases (according to the type).

The product identification codes are labelled on each package.

Storage

You are advised to store the product in a dry, closed location, protected from atmospheric agents.



Reference standard:
En 14303:2009+A1:2013
Certificate No. 0407-CPR-1230.

TEKNISOL srl
via 1° Maggio, 38/38A - 20028 San Vittore Olona
Milano – Italia | 0039 0331 514605 | info@teknisol.it

